- 1 LISTING OF CLAIMS
- 2 CLAIMS
- 3 What is claimed is:
- 4 1. (Original) A method for encrypting a plain-text message, the method comprising:
- 5 generating a first random number;
- 6 transforming said first random number into a first pseudo random number;
- 7 further expanding a randomness of said first random number and/or said first pseudo random
- 8 number into a set of pair-wise differentially-uniform pseudo random numbers;
- 9 dividing said plain-text message into a plurality of plain-text blocks;
- 10 encrypting said plain-text blocks to form a plurality of cipher-text blocks;
- combining said plurality of plain-text blocks into at least one check sum; and
- 12 employing said set of pair-wise differentially-uniform pseudo random numbers, together with
- said first random number and/or said first pseudo random number, to embed a message integrity
- 14 check in said cipher-text blocks.
- 2. (currently amended) A method as recited in claim 1, wherein the step of encrypting said
- 16 plain-text blocks includes employing the said first random number, and/or said first pseudo
- 17 random number, and/or said set of pair-wise differentially-uniform pseudo random numbers.

- 3. (Original) A method as recited in claim 1, wherein the step of employing includes pairing said
- 2 first random number, and/or said first pseudo random number, and/or said set of pair-wise
- 3 differentially-uniform pseudo random numbers, with said plurality of cipher-text blocks; and
- 4 combining each pair to form a plurality of output blocks.
- 5 4. (Original) A method as recited in claim 3, wherein the step of combining each pair includes
- 6 performing an exclusive-or operation upon components of said each pair.
- 5. (Original) A method as recited in claim 1, wherein the step of encrypting includes encrypting
- 8 said first random number.
- 9 6. (Original) A method as recited in claim 1, wherein the step of encrypting includes encrypting
- 10 said check sum.
- 7. (Original) A method as recited in claim 1, wherein the step of combining includes obtaining
- said check sum from an exclusive-or of said plurality of plain-text blocks.
- 13 8. (Original) A method as recited in Claim 1, wherein the step of transforming said random
- 14 number includes a non-cryptographic or linear operation.
- 9. (Original) A method as recited in Claim 1, wherein the step of transforming said random
- 16 number includes a cryptographic operation.
- 17 10. ((currently amended) A method as recited in Claim 1, wherein the said set of pair-wise
- differentially-uniform numbers are set of pair-wise differentially-uniform numbers in GFp.
- 19 11. (Original) A method as recited in claim 2, wherein the step of employing includes:

- 1 pairing said first random number, and/or said first pseudo random number, and/or said set of
- 2 pair-wise differentially-uniform pseudo random numbers, with said plurality of plain-text blocks;
- 3 and
- 4 combining each pair to form a plurality of input blocks used in said step of encrypting.
- 5 12. (Original) A method as recited in claim 11, wherein the step of combining each pair includes
- 6 performing an exclusive-or operation upon components of said each pair.
- 7 13. (Original) A method for decrypting a cipher-text message, the method comprising:
- 8 dividing said cipher-text message into a plurality of cipher-text blocks;
- 9 decrypting said cipher-text blocks in forming a plurality of plain-text blocks;
- transforming at least one of said plain-text blocks into a first pseudo random number:
- 11 further expanding at least one of said plain-text blocks and/or said first pseudo random number
- into a set of pair-wise differentially-uniform pseudo random numbers;
- combining said first pseudo random number, and/or said set of pair-wise differentially-uniform
- 14 pseudo random numbers, and/or said at least one plain-text block to form at least two check sums
- and to form a plurality of output blocks; and
- comparing said at least two check sums in declaring success of a message integrity check.
- 17 14. (Original) A method as recited in claim 13, wherein the step of decrypting said cipher-text
- 18 blocks includes employing said first pseudo random number, and/or said set of pair-wise
- 19 differentially-uniform pseudo random numbers.

- 1 15. (Original) A method as recited in claim 13, wherein the step of combining includes:
- 2 pairing said first pseudo random number, and/or said set of pair-wise differentially-uniform
- 3 pseudo random numbers, with said plurality of plain-text blocks; and
- 4 using each pair to form a plurality of output blocks and employing the output blocks to form said
- 5 at least two check sums.
- 6 16. (Original) A method as recited in claim 15, wherein the step of using each pair includes
- 7 performing an exclusive-or operation upon components of said each pair.
- 8 17. (currently amended) A method as recited in claim 15, wherein the step of forming includes:
- 9 dividing the said output blocks into at least two subsets, and
- 10 obtaining said at least two checksums from an exclusive-or of said subsets of output blocks.
- 11 18. (Original) A method as recited in Claim 13, wherein the step of transforming said plain-text
- 12 blocks includes a non-cryptographic or linear operation.
- 13 19. (Original) A method as recited in Claim 13, wherein the step of transforming said plain-text
- 14 blocks includes a cryptographic operation.
- 20. (currently amended) A method as recited in Claim 13, wherein the said set of pair-wise
- 16 differentially-uniform numbers are set of pair-wise differentially-uniform numbers in GFp.
- 17 21. (Original) A method as recited in claim 14, wherein the step of employing includes:

- 1 pairing said first random number, and/or said first pseudo random number, and/or said set of
- 2 pair-wise differentially-uniform pseudo random numbers, with said plurality of cipher-text
- 3 blocks; and
- 4 combining each pair to form a plurality of input blocks used in said step of decrypting.
- 5 22. (Original) A method as recited in claim 3, wherein p is a prime number, and the step of
- 6 combining each pair includes performing a modulo p addition upon components of said each
- 7 **р**аіт.
- 8 23. (Original) A method as recited in claim 11, wherein p is a prime number, and the step of
- 9 combining each pair includes performing a modulo p addition upon components of said each
- 10 pair.
- 24. (Original) A method as recited in claim 15, wherein p is a prime number, and the step of
- using each pair includes performing a modulo p addition upon components of said each pair.
- 25. (Original) A method as recited in claim 21, wherein p is a prime number, and the step of
- 14 combining each pair includes performing a modulo p addition upon components of said each
- 15 pair.
- 16 26. (Original) An article of manufacture comprising a computer usable medium having
- 17 computer readable program code means embodied therein for causing encryption of a plain-text
- 18 message, the computer readable program code means in said article of manufacture comprising
- computer readable program code means for causing a computer to effect the steps of claim 1.
- 20 27. (Original) An article of manufacture comprising a computer usable medium having
- 21 computer readable program code means embodied therein for causing decryption of a cipher-text
- 22 message, the computer readable program code means in said article of manufacture comprising
- computer readable program code means for causing a computer to effect the steps of claim 13.

- 1 28. (Original) A computer program product comprising a computer usable medium having
- 2 computer readable program code means embodied therein for causing encryption of a plain-text
- 3 message, the computer readable program code means in said computer program product
- 4 comprising computer readable program code means for causing a computer to effect the steps of
- 5 claim 1.
- 6 29. (Original) A computer program product comprising a computer usable medium having
- 7 computer readable program code means embodied therein for causing decryption of a plain-text
- 8 message, the computer readable program code means in said computer program product
- 9 comprising computer readable program code means for causing a computer to effect the steps of
- 10 claim 13.
- 30. (Original) A program storage device readable by machine, tangibly embodying a program of
- instructions executable by the machine to perform method steps for encrypting a plain-text
- message, said method steps comprising the steps of claim 1.
- 14 31. (Original) A program storage device readable by machine, tangibly embodying a program of
- instructions executable by the machine to perform method steps for decrypting a cipher-text
- message, said method steps comprising the steps of claim 13.
- 17 32. (Currently Amended) A method for encryption/decryption of a plain-text message, the
- 18 method comprising the steps of:
- 19 generating a first random number;
- 20 transforming said first random number into a first pseudo random number;
- 21 further expanding a randomness of said first random number and/or said first pseudo random
- 22 number into a set of pair-wise differentially-uniform pseudo random numbers:

- dividing the plain-text message into a plurality of plain-text blocks:
- 2 encrypting said plain-text blocks in forming a plurality of cipher-text blocks;
- 3 combining said plurality of plain-text blocks into at least one check sum; and
- 4 employing said first random number, said first pseudo random number and said set of pair-wise
- 5 differentially-uniform pseudo random numbers to embed a message integrity check in said
- 6 cipher-text blocks to form a cipher-text message; and
- 7 dividing said cipher-text message into a plurality of cipher-text blocks to form an encryption of
- 8 said plain-text message;
- 9 decrypting said cipher-text blocks in forming a plurality of plain-text blocks;
- transforming at least one of said plain-text blocks into a first pseudo random number;
- 11 further expanding at least one of said plain-text blocks and/or said first pseudo random number
- 12 into a set of pair-wise differentially-uniform pseudo random numbers;
- 13 combining said first pseudo random number, and/or said set of pair-wise differentially-uniform
- 14 pseudo random numbers, and/or said at least one plain-text block to form at least two check sums
- 15 and to re-form the said plain-text message; and
- 16 comparing said at least two check sums in declaring success of a message integrity check in
- 17 decryption of said cipher-text to reform said plain-text message.
- 18 33. (Original) An apparatus to encrypt a plain-text message, the apparatus comprising:

- 1 a Randomness Generator to generate a first random number;
- 2 a Randomness Transformer to transform said first random number into a first pseudo random
- 3 number;
- 4 a Pairwise Additively Uniform Sequence Generator to further expand a randomness of said first
- 5 random number and/or said first pseudo random number into a set of pair-wise
- 6 differentially-uniform pseudo random numbers;
- 7 an Encryptor to divide said plain-text message into a plurality of plain-text blocks, and to encrypt
- 8 said plain-text blocks to form a plurality of cipher-text blocks;
- 9 a Checksum Generator to combine said plurality of plain-text blocks into at least one check sum;
- 10 and
- an Integrity Extractor and Checker to employ said set of pair-wise differentially-uniform pseudo
- 12 random numbers, together with said first random number and/or said first pseudo random
- number, to embed a message integrity check in said cipher-text blocks.
- 14 34. (Original) An apparatus to decrypt a cipher-text message, the apparatus comprising:
- 15 a Decryptor to divide said cipher-text message into a plurality of cipher-text blocks, and to
- 16 decrypt said cipher-text blocks in forming a plurality of plain-text blocks;
- 17 a Randomness Transformer to transform at least one of said plain-text blocks into a first pseudo
- 18 random number;
- 19 a Pairwise Additively Uniform Sequence Generator to further expand at least one of said
- 20 plain-text blocks and/or said first pseudo random number into a set of pair-wise
- 21 differentially-uniform pseudo random numbers;

DOCKET NUMBER: YOR920000763US1

- a Checksum Generator to combine said first pseudo random number, and/or said set of pair-wise
- 2 differentially-uniform pseudo random numbers, and/or said at least one plain-text block to form
- 3 at least two check sums and to form a plurality of output blocks; and
- 4 an Integrity Extractor and Checker to compare said at least two check sums in declaring success
- 5 of a message integrity check.
- 6 35. (Original) An article of manufacture comprising a computer usable medium having
- 7 computer readable program code means embodied therein for causing encryption of a plain-text
- 8 message, the computer readable program code means in said article of manufacture comprising
- 9 computer readable program code means for causing a computer to effect the steps of claim 2.
- 10 36. (Original) An article of manufacture comprising a computer usable medium having
- computer readable program code means embodied therein for causing decryption of a cipher-text
- 12 message, the computer readable program code means in said article of manufacture comprising
- computer readable program code means for causing a computer to effect the steps of claim 14.
- 14 37. (Original) A computer program product comprising a computer usable medium having
- 15 computer readable program code means embodied therein for causing encryption of a plain-text
- 16 message, the computer readable program code means in said computer program product
- 17 comprising computer readable program code means for causing a computer to effect the steps of
- 18 claim 2.
- 19 38. (Original) A computer program product comprising a computer usable medium having
- 20 computer readable program code means embodied therein for causing decryption of a plain-text
- 21 message, the computer readable program code means in said computer program product
- 22 comprising computer readable program code means for causing a computer to effect the steps of
- 23 claim 14.

- 39. (Original) A program storage device readable by machine, tangibly embodying a program of
- 2 instructions executable by the machine to perform method steps for encrypting a plain-text
- message, said method steps comprising the steps of claim 2.
- 4 40. (Original) A program storage device readable by machine, tangibly embodying a program of
- 5 instructions executable by the machine to perform method steps for decrypting a cipher-text
- 6 message, said method steps comprising the steps of claim 14.
- 7 41. (Original) A method as recited in claim 3, wherein the step of combining each pair includes
- 8 performing an addition in a group upon components of said each pair.
- 9 42. (Currently Amended) A method as recited in claim 11, wherein the step of combining each
- pair includes performing an addition in a group upon components of said each pair.
- 11 43. (Original) A method as recited in claim 15, wherein the step of using each pair includes
- 12 performing an addition in a group upon components of said each pair.
- 13 44. (Original) A method as recited in claim 21, wherein the step of combining each pair includes
- 14 performing an exclusive-or operation upon components of said each pair.
- 15 45. (Original) A method as recited in claim 21, wherein the step of combining each pair includes
- 16 performing an addition in a group upon components of said each pair.
- 17 46. (new) A method as recited in Claim 33, wherein at least one element performs a plurality of
- 18 operations in parallel.
- 19 47. (new) A method as recited in Claim 1, wherein the step of encrypting said plain-text blocks
- is performed in parallel for a plurality of said plain-text blocks.